

# 3000 Series Exit Devices

## Premier Product

### Certification & Compliance:

- ANSI/BHMA A156.3, Grade 1
- ANSI A117.1 Accessibility Code
- Underwriters Laboratories (UL and CUL) listed for accident hazard (panic) standard.
- Fire Exit hardware for hollow metal doors, UL and CUL listed for 3 hour, A label and lesser doors, Prefix "F" before part number.
- Fire Exit hardware for wood doors, listed up to 1-1/2 hour, B label doors.
- All exit devices comply with life safety code NFPA 101.
- All fire rated devices comply with fire door and window code NFPA80.

**3880**  
Rim Exit Device

**3900**  
Mortise Exit Device

**3700 Surface**  
Vertical Rod Exit Device



### General Specifications:

	<b>3700</b>	<b>3880</b>	<b>3900</b>
<b>Chassis</b>	Non-ferrous alloy	Non-ferrous alloy	Non-ferrous alloy
<b>Chassis cover</b>	Cold drawn brass, bronze or stainless steel	Cold drawn brass, bronze or stainless steel	Cold drawn brass, bronze or stainless steel
<b>Door Types</b>	Wood or metal	Wood or metal	Wood or Metal
<b>Door Thickness</b>	1-3/4" (44.45mm) standard up to 2-1/4" (57.15mm) available	1-3/4" (44.45mm) standard up to 2-1/4" (57.15mm) available	1-3/4" (44.45mm) standard up to 2-1/4" (57.15mm) available
<b>Stile</b>	4-1/2" (144.30mm) minimum with trim, 3-1/2" (88.90mm) minimum without trim.	See trim page for stile dimensions	4-1/2" (144.30mm) minimum
<b>Mounting</b>	Supplied with wood and machine screws. Available with thru bolts.	Supplied with wood and machine screws. Available with thru bolts	Supplied with wood and machine screws. Available with thru bolts.
<b>Handing</b>	Handed. Specify LHRB or RHRB	Handed. Specify LHRB or RHRB	Handed. Specify LHRB or RHRB.
<b>Dogging</b>	Allen type standard. Available with cylinder dogging (suffix "CD")	Allen type standard. Available with cylinder dogging (suffix CD)	Allen type standard. Available w/ cylinder dogging (suffix CD)
<b>Top/Bottom Bolts</b>	Brass	N/A	N/A
<b>Latchbolt</b>	N/A	Stainless steel, 3/4" (19.05mm) throw	Brass, 3/4" (19.05mm) throw
<b>Rail</b>	Roll-formed brass, bronze or stainless steel	Roll-formed brass, bronze or stainless steel	Roll-formed brass, bronze or stainless steel
<b>Rail Projection</b>	3-1/4" (82.55mm) maximum	3-1/4" (82.55mm) maximum	3-1/4" (82.55mm) maximum
<b>Opening Height</b>	90" (2286.00mm) standard	N/A	N/A
<b>Fire Exit Hardware-up to:</b>	4' x 8' single door 8' x 8' pairs of doors	4' x 8' single door 8' x 8' pairs of doors with S21 mullion.	4' x 10' single 8' x 10' pairs of doors (with 3600-FR) 8' x 8' pairs of doors (with 3700-FR)
<b>Trim</b>	See trim pages 110, 111	See trim pages 110, 111	See trim pages 110, 111
<b>Finishes</b>	AL, US3, US4, US10, US10B, US10BL, US32, US32D	AL, US3, US4, US10, US10B, US10BL, US32, US32D	AL, US3, US4, US10, US10B, US10BL, US32, US32D

### Order Example:

**Example:** To order 3880 Rim Exit Device with SL Trim.

**Specify:**

**Standard:**

**38**

Series

**88**

Function

**SL**

Outside Trim  
(If Applicable)

**26D**

Outside Finish

**F**

Rail Size

**32D**

Push Bar Finish

**RR**

Handing












**xxx**

Options  
(If Required)

# 3000 Series Exit Devices

## Premier Product

### 3000 Series Functions: Standard Strikes

<p><b>3700 Series</b></p>	<p><b>S646 Standard &amp; Fire Rated Top Strike</b></p> <p>Surface applied top strike. No mortise required. Nylon Coated. Furnished standard.</p> 	<p><b>S23 Bottom Strike</b></p>  <p>Standard strike. Surface applied to threshold or floor. Black nylon coated.</p>	<p><b>S60</b></p>  <p>For mounting top plate on doors with flush panel heads.</p>	
<p><b>3700 Series</b></p>	<p><b>S43 Bottom Strike</b></p>  <p>Standard for SB3700. Alternate for S3700. No mortise required. Black nylon coated.</p>			
<p><b>3800 Series</b></p>	<p><b>S38</b></p>  <p>Standard strike for 3800. Surface applied.</p>	<p><b>S39</b></p>  <p>Alternate for 3800. Fully mortised. Dimension "L" equal to 1/2" greater than door thickness. Nylon coating on lip only.</p>	<p><b>S36</b></p>  <p>Double door strike. Alternate for 3800. Use on a pair of doors with a mullion.</p>	<p><b>S31</b></p>  <p>Alternate for 3800. Half mortised. Nylon coating on face only.</p>
<p><b>3900 Series</b></p>	<p><b>S48C</b></p>  <p>Standard for S3900. Curved lip ANSI A115.1. Handed. 1 1/4" lip standard. Longer lips available in 1/4" increments up to 2 7/8".</p>	<p><b>S48</b></p>  <p>Alternate for S3900. Flat lip ANSI A115.1. Non-handed. 1 1/4" lip standard. Longer lips available in 1/4" increments up to 2 7/8".</p>	<p><b>S47</b></p>  <p>Alternate for S3900. Open back ANSI A115.14. Beveled 1/8" in 2". Handed. Specify hand of active door.</p>	

# 4000 Series Exit Devices

## Premier Product

### Certification & Compliance:

- ANSI/BHMA A156.3, Grade 1
- ANSI A117.1 Accessibility Code
- Underwriters Laboratories (UL and CUL) listed for accident hazard (panic) standard.
- Fire Exit hardware for hollow metal doors, UL and CUL listed for 3 hour, A label and lesser doors, Prefix "F" before part number.
- Fire Exit hardware for wood doors, listed up to 1-1/2 hour, B label doors.
- All exit devices comply with life safety code NFPA 101.
- All fire rated devices comply with fire door and window code NFPA80.



**4800**  
Narrow Stile Rim Exit Device



**4900**  
Narrow Stile Mortise Device

### General Specifications:

	<b>4800</b>	<b>4900</b>
<b>Chassis</b>	Non-ferrous alloy	Non-ferrous alloy
<b>Chassis cover</b>	Cold drawn brass, bronze or stainless steel	Cold drawn brass, bronze or stainless steel
<b>Door Types</b>	Wood, hollow metal or extruded aluminum	Wood or hollow metal
<b>Door Thickness</b>	1-3/4" (44.45mm) minimum	1-3/4" (44.45mm) standard, up to 2-1/4" (57.15mm) available
<b>Stile</b>	1-3/4" (44.45mm) minimum	4-1/2" (114.30mm) minimum
<b>Mounting</b>	Supplied with wood and machine screws. Available with thru bolts.	Supplied with wood and machine screws. Available with thru bolts.
<b>Handing</b>	Handed. Specify LHRB or RHRB	Handed. Specify LHRB or RHRB
<b>Dogging</b>	Allen-type standard. Available with cylinder dogging (suffix CD)	Allen-type standard. Available with cylinder dogging (suffix CD)
<b>Top/bottom bolts</b>	N/A	N/A
<b>Latchbolt</b>	Stainless steel, 3/4" (19.05mm) throw	Brass, 3/4" (19.05 mm) throw
<b>Rail</b>	Roll formed brass, bronze or stainless steel	Roll formed brass, bronze or stainless steel
<b>Rail Projection</b>	3-1/4" (82.55mm) maximum	3-1/4" (82.55mm) maximum
<b>Opening Height</b>	N/A	N/A
<b>Fire Exit Hardware—up to:</b>	N/A	4' x 8' single door 8' x 8' pairs of doors
<b>Trim</b>	See trim pages 110, 111	See trim pages 110, 111
<b>Finishes</b>	US3, US4, US10, US10B, US10BL, US32, US32D	US3, US4, US10, US10B, US10BL, US32, US32D

### Order Example:

**Example:** To order 4800 Narrow Stile Rim Exit Device with SL Trim.

**Specify:**

<b>Standard:</b>	<b>48</b>	<b>08</b>	<b>SL</b>	<b>26D</b>	<b>F</b>	<b>32D</b>	<b>RR</b>	<b>xxx</b>
	Series	Function	Outside Trim (If Applicable)	Outside Finish	Rail Size	Push Bar Finish	Handing	Options (If Required)