


8800 Functions and Trims

80 Series

Options	Series	Function	Rail Lgth	Trim	Hand	Outside Finish	Inside Finish	Door Width	Options																																																																
F1-83-56	88	13	F	ETL	RHR	26D	32D	36"	8800																																																																
700 Series ET Trim																																																																									
 <p>Exits with ET Trim, specify lever design after the ET designation (e.g., ETL)</p>																																																																									
<table border="1"> <thead> <tr> <th>SARGENT Function Numbers</th> <th>ANSI Function Numbers</th> <th>Description & Cylinder Info (1-3/4" Door)</th> <th>ANSI Type 1 8800 Panic & Fire</th> </tr> </thead> <tbody> <tr> <td>04</td> <td>03</td> <td>Night Latch Key Retracts Latch #34 Cylinder Supplied</td> <td>8804 x ET_</td> </tr> <tr> <td>06</td> <td>09</td> <td>Key unlocks Trim, Trim retracts latch/ Trim relocks when key is removed #41 Cylinder Supplied</td> <td>8806 x ET_</td> </tr> <tr> <td>10</td> <td>01</td> <td>No outside operation (No Cylinder)</td> <td>8810</td> </tr> <tr> <td>10</td> <td>02</td> <td>No outside operation (No Cylinder) ET Control is used as Pull Only</td> <td>8810 x ET_</td> </tr> <tr> <td>13</td> <td>08</td> <td>Key Outside Unlocks/locks Trim #41 Cylinder Supplied</td> <td>8813 x ET_</td> </tr> <tr> <td>15</td> <td>14</td> <td>Passage Only (No cylinder)</td> <td>8815 x ET_</td> </tr> <tr> <td>16</td> <td>10</td> <td>Key Outside Retracts Latch; Key Inside Unlocks/Locks O/S Trim O/S #34 Cylinder & I/S #44 Cylinder Supplied</td> <td>8816 x ET_</td> </tr> <tr> <td>40</td> <td>02</td> <td>Freewheeling Trim - No outside operation (No Cylinder) Dummy Trim</td> <td>8840 x ET_</td> </tr> <tr> <td>43</td> <td>08</td> <td>Freewheeling Trim - Key Outside Unlocks/locks Trim #41 Cylinder Supplied</td> <td>8843 x ET_</td> </tr> <tr> <td>44</td> <td>03</td> <td>Freewheeling Trim - Key Retracts Latch #34 Cylinder Supplied</td> <td>8844 x ET_</td> </tr> <tr> <td>46</td> <td>09</td> <td>Freewheeling Trim - Key unlocks Trim, Trim retracts latch/ Trim relocks when key is removed #41 Cylinder Supplied</td> <td>8846 x ET_</td> </tr> <tr> <td>73</td> <td></td> <td>Electrified ET Trim - Fail Safe Power Off, Unlocks Lever (No Cylinder)</td> <td>8873 x ET_</td> </tr> <tr> <td>74</td> <td></td> <td>Electrified ET Trim - Fail Secure Power Off, Locks Lever (No Cylinder)</td> <td>8874 x ET_</td> </tr> <tr> <td>75</td> <td></td> <td>Electrified ET Trim - Fail Safe Power Off, Unlocks Lever, Key Retracts Latch #34 Cylinder Supplied</td> <td>8875 x ET_</td> </tr> <tr> <td>76</td> <td></td> <td>Electrified ET Trim - Fail Secure Power Off, Locks Lever, Key Retracts Latch #34 Cylinder Supplied</td> <td>8876 x ET_</td> </tr> </tbody> </table>										SARGENT Function Numbers	ANSI Function Numbers	Description & Cylinder Info (1-3/4" Door)	ANSI Type 1 8800 Panic & Fire	04	03	Night Latch Key Retracts Latch #34 Cylinder Supplied	8804 x ET_	06	09	Key unlocks Trim, Trim retracts latch/ Trim relocks when key is removed #41 Cylinder Supplied	8806 x ET_	10	01	No outside operation (No Cylinder)	8810	10	02	No outside operation (No Cylinder) ET Control is used as Pull Only	8810 x ET_	13	08	Key Outside Unlocks/locks Trim #41 Cylinder Supplied	8813 x ET_	15	14	Passage Only (No cylinder)	8815 x ET_	16	10	Key Outside Retracts Latch; Key Inside Unlocks/Locks O/S Trim O/S #34 Cylinder & I/S #44 Cylinder Supplied	8816 x ET_	40	02	Freewheeling Trim - No outside operation (No Cylinder) Dummy Trim	8840 x ET_	43	08	Freewheeling Trim - Key Outside Unlocks/locks Trim #41 Cylinder Supplied	8843 x ET_	44	03	Freewheeling Trim - Key Retracts Latch #34 Cylinder Supplied	8844 x ET_	46	09	Freewheeling Trim - Key unlocks Trim, Trim retracts latch/ Trim relocks when key is removed #41 Cylinder Supplied	8846 x ET_	73		Electrified ET Trim - Fail Safe Power Off, Unlocks Lever (No Cylinder)	8873 x ET_	74		Electrified ET Trim - Fail Secure Power Off, Locks Lever (No Cylinder)	8874 x ET_	75		Electrified ET Trim - Fail Safe Power Off, Unlocks Lever, Key Retracts Latch #34 Cylinder Supplied	8875 x ET_	76		Electrified ET Trim - Fail Secure Power Off, Locks Lever, Key Retracts Latch #34 Cylinder Supplied	8876 x ET_
SARGENT Function Numbers	ANSI Function Numbers	Description & Cylinder Info (1-3/4" Door)	ANSI Type 1 8800 Panic & Fire																																																																						
04	03	Night Latch Key Retracts Latch #34 Cylinder Supplied	8804 x ET_																																																																						
06	09	Key unlocks Trim, Trim retracts latch/ Trim relocks when key is removed #41 Cylinder Supplied	8806 x ET_																																																																						
10	01	No outside operation (No Cylinder)	8810																																																																						
10	02	No outside operation (No Cylinder) ET Control is used as Pull Only	8810 x ET_																																																																						
13	08	Key Outside Unlocks/locks Trim #41 Cylinder Supplied	8813 x ET_																																																																						
15	14	Passage Only (No cylinder)	8815 x ET_																																																																						
16	10	Key Outside Retracts Latch; Key Inside Unlocks/Locks O/S Trim O/S #34 Cylinder & I/S #44 Cylinder Supplied	8816 x ET_																																																																						
40	02	Freewheeling Trim - No outside operation (No Cylinder) Dummy Trim	8840 x ET_																																																																						
43	08	Freewheeling Trim - Key Outside Unlocks/locks Trim #41 Cylinder Supplied	8843 x ET_																																																																						
44	03	Freewheeling Trim - Key Retracts Latch #34 Cylinder Supplied	8844 x ET_																																																																						
46	09	Freewheeling Trim - Key unlocks Trim, Trim retracts latch/ Trim relocks when key is removed #41 Cylinder Supplied	8846 x ET_																																																																						
73		Electrified ET Trim - Fail Safe Power Off, Unlocks Lever (No Cylinder)	8873 x ET_																																																																						
74		Electrified ET Trim - Fail Secure Power Off, Locks Lever (No Cylinder)	8874 x ET_																																																																						
75		Electrified ET Trim - Fail Safe Power Off, Unlocks Lever, Key Retracts Latch #34 Cylinder Supplied	8875 x ET_																																																																						
76		Electrified ET Trim - Fail Secure Power Off, Locks Lever, Key Retracts Latch #34 Cylinder Supplied	8876 x ET_																																																																						
<p>Lever Designs for ET Controls A, B, E, F, J, L, P, W Also available with Coastal Series & Studio Collection Levers</p>																																																																									
<p>ET Designation with Suffix (Used to order ET without device) 8800 Series: 704, 706-8, 710, 713-8, 715-8, 716, 740, 743-8, 744, 746-8, 773-8, 774-8, 775-8 & 776-8</p>																																																																									
<p>Freewheeling Trim The lever rotates when the door is locked preventing excessive force from being applied to the horizontal lever</p>																																																																									
<p>Electrified ET Trim Voltage must be specified for the following functions: 73, 74, 75 and 76. Specify: 12VDC or 24VDC</p>																																																																									

Mechanical Options:

- 12-
- 16-
- 19-
- 31-
- 36-
- 37-
- 43-
- 53-
- 54-
- 55-
- 56-
- 56-HK-
- 57-
- 58-
- 59-
- BC-59-
- 76-
- 85-
- 86-
- 87-
- AL-
- BT-
- CPC-
- GL-
- LD-
- PL-
- ** SG-
- TB-
- TL-

Cylinder Options:

- 10-
- 10-21-
- 10-63-
- 11-
- 11-21-
- 11-60-
- 11-63-
- 11-64-
- 11-70-7P-
- 11-72-7P-
- 11-73-7P-
- 11-65-73-7P-
- 21-
- 22-
- 51-
- 52-
- 60-
- 63-
- 64-
- 70-
- 72-
- 73-
- 65-73-
- 65-73-7P-
- 73-7P-
- 81-
- 82-
- F1-82-
- 83-
- F1-83-
- 84-
- BR-
- LC-
- *SC-
- *SE-

Note: Exit devices are available in all standard finishes, except 14, 15, 26 & 26D. With these finishes, exit devices are supplied in 32 or 32D to match accordingly. 32 or 32D is automatically supplied when 26 or 26D is specified. For nickel finishes, specify 14/32 or 15/32D to receive nickel finished trims and stainless exit devices

Pull & Thumbpiece Trim Section

Trim Designations

- Use three letter designations (Ex "PTB") when ordering the Exit Device with trim
- Use the six digit designation (Ex "866-MAL") when ordering trim without an Exit Device, always specify finish

Series



SARGENT Function Numbers	ANSI Function Numbers	Description & Cylinder Info. (1-3/4" Door)	814-FSL*	814-FSW*	814-MSL*	814-PSB*	814-ST5	862 Pull	8800 Panic & Fire
04	03	Night Latch Key Retracts Latch #34 Cylinder Supplied	814-FSL*	814-FSW*	814-MSL*	814-PSB*	814-ST5	862 Pull	8804 x Trim Designation
10	02	No O/S Operation or Cylinder (Pull Only)	810-FLL	810-FLW	810-MAL	810-PTB	810-ST5	862 Pull	8810 x Trim Designation
28	15	Passage Only (No cylinder)	828-FLL	828-FLW	828-MAL	828-PTB	828-ST5	N/A	8828 x Trim Designation
63	05	Key Outside Unlocks/ Locks Thumbpiece #34 Cylinder Supplied	866-FLL	866-FLW	866-MAL	866-PTB	866-ST5	N/A	8863 x Trim Designation
66	07	Key Outside Retracts Latch; Key Inside Unlocks/Locks O/S Trim O/S #34 & I/S #44	866-FLL	866-FLW	866-MAL	866-PTB	866-ST5	N/A	8866 x Trim Designation

* FSL, FSW, MSL and PSB trims are used with (HC-& 12-) 8888 and 8804 only and are the same as FLL, FLW, MAL and PTB pulls except for cylinder hole located 3/8" (9mm) lower.

Note: Thumbpiece trims for 63 and 66 function devices are identical and are identified as 66 function when trim is ordered separately.

Note: FLW & FSW trims are not available in 32(629) or 32D(630)

* Options are not available with 8816

** Only available with 15, 26D and 32D finishes

Available Finishes

SARGENT Finishes	BHMA Finishes
03	605
04	606
09	611
10	612
10B	613
10BE	613E
10BL	614
14	618
15	619
20D	624
26	625
26D	626
32	629
32D	630