


Latch front adapter
A501-878



Used to convert 1" (25 mm) wide square front faceplates for 1¹/₈" (29 mm) wide door preparations. Furnished in black plastic. Order in multiples of 100.

Sleeve
G506-815



Used on 7/8" (22 mm) diameter latch housings in 1" (25 mm) edge bore. Furnished standard with complete locks.

Door reinforcement

Schlage reinforcing units help prevent the collapse of hollow metal doors when locksets are tightly mounted.




A501-565
1³/₈" (35 mm) doors
or
A501-566
1¹/₄" (44 mm) doors

Strikes

Deadbolt strikes

Part number	Lip length	Description
10-055	--	1 ¹ / ₈ " x 2 ³ / ₄ " (29 mm x 70 mm) square corner, box, standard
10-064		1 ³ / ₁₆ " (30 mm) diameter, circular drive-in, thimble strike, 494 (for 626) only
10-092	1 ¹ / ₈ " (29 mm)	1 ⁵ / ₈ " x 2 ¹ / ₄ " (41 mm x 57 mm) 1/4" (6 mm) radius round corner, full lip, no box
10-095		1 ⁵ / ₈ " x 2 ¹ / ₄ " (41 mm x 57 mm) square corner, full lip, no box


10-055




10-064



10-092




10-095




Deadlatch strikes

Part number	Lip length	Description
10-001	1 ¹ / ₈ " (29 mm)	1 ¹ / ₈ " x 2 ³ / ₄ " (29 mm x 70 mm) square corner, T-strike, box, standard
10-004		1 ¹ / ₈ " x 2 ³ / ₄ " (29 mm x 70 mm) 1/4" (6 mm), radius round corner, T-Strike, box
10-026		1 ⁵ / ₈ " x 2 ¹ / ₄ " (41 mm x 57 mm) square corner, full lip, no box
10-027	1 ⁷ / ₃₂ " (31 mm)	1 ⁵ / ₈ " x 2 ¹ / ₄ " (41 mm x 57 mm) 1/4" (6 mm) radius round corner, full lip, no box
10-058		1 ³ / ₄ " (44 mm) diameter, circular, adjustable, 605 and 626 only


10-001




10-026



10-027



10-058



Deadbolt/deadlatch strikes combinations

Combo number	Deadbolt strike	Deadlatch strike
10-250	10-055	10-001, 1 ¹ / ₈ " (29 mm) lip
10-251	10-064	10-001, 1 ¹ / ₈ " (29 mm) lip
10-252	10-055	10-026
10-253	10-064	10-026
10-255	10-055	10-027
10-256	10-064	10-027
10-257	10-092	10-027
10-258	10-064	10-058
10-259	10-095	10-026